

# FEULING OIL PUMP CORPORATION

## FEULING CAMPLATE & OIL PUMP OPTIONAL FASTENER KIT INSTALLATION INSTRUCTIONS

FOR H-D TWIN CAM® ENGINES EQUIPPED WITH FEULING OIL PUMP AND CAMPLATE



- OPTIONAL FEULING CAMPLATE/OIL PUMP FASTENER KIT FOR TWIN CAM® ENGINES
- QUALITY 12-POINT STAINLESS STEEL BOLTS FOR THE FEULING CAMPLATE AND FEULING OIL PUMP
- FEATURE PRECISION ROLLED THREADS FOR OPTIMUM ENGAGEMENT, PREVENTS GALLING AND PROMOTES MORE CONSISTENT TORQUE LOADING.
- WIDE UNDER HEAD FLANGE DESIGN PROVIDES EVEN LOAD DISTRIBUTION FOR OPTIMUM SEALING OF SURFACES
- MANUFACTURED BY ARP® TO FEULING'S EXACT SPECIFICATIONS
- INCLUDES ASSEMBLY LUBRICANT FOR INSTALLATION - MADE IN THE U.S.A.

### **Part # 8020**

#### **IMPORTANT NOTICE**

THIS INSTALLATION SHOULD BE DONE BY AN EXPERIENCED MECHANIC WHO HAS ACCESS TO A FACTORY SERVICE MANUAL AND ALL REQUIRED TOOLS. THIS PROCEDURE REQUIRES USE OF SPECIALTY TOOLS.

#### **CAUTION**

INCORRECT INSTALLATION CAN CAUSE ENGINE DAMAGE NOT COVERED UNDER WARRANTY. FAILURE TO INSTALL COMPONENTS CORRECTLY CAN CAUSE ENGINE SEIZURE. ENGINE SEIZURE MAY RESULT IN SERIOUS INJURY TO MOTORCYCLE, OPERATOR, PASSENGER, AND/OR OTHERS.

#### **CAUTION**

IMPROPERLY TORQUED BOLTS MAY RESULT IN OIL LEAKS AND DISTORTION OF THE CAMPLATE AND OIL PUMP.

***THIS FASTNER KIT IS ONLY FOR USE WITH THE FEULING OIL PUMPS AND CAMPLATE***

- 1 Refer to the proper service manual for your model motorcycle engine.
- 2 Always use new O-rings
- 3 Clean and inspect case and oil pump holes and threads
- 4 Clean and inspect new Feuling hardware
- 5 Lightly coat the threads and under head flange of the new Feuling bolts with the supplied moly lube.
- 6 Bolt the complete Feuling Oil Pump including sub seal to the camplate only finger tight with the pressure housing of the pump facing the camplate using the 1 ¼" bolts.
- 7 Check O-rings for proper installation on the case and oil pump.

7 Thread a 3/8" – 16 nut onto cylinder stud

8 Thread a second nut onto cylinder stud until it contacts the first

9 Turning the second nut installed alternately tighten each cylinder stud to 5 ft. lbs.

10 Following the same sequence final torque each stud to 10 ft. lbs.

11 Lightly coat the threads of the cylinder studs, head bolt and bottom face of the head bolts with the supplied moly assemble lubricant.

12 Start the head bolts onto the cylinder studs – the 2 short bolts on the left side of the head and the 2 long bolts on the right side of the head.

13 Alternately turn each cylinder head bolt until finger tight.

14 Using the sequence shown in your service manual, torque the head bolts in the following steps 10 ft. lbs. 20 ft. lbs. 25 ft. lbs. 30 ft. lbs. and final torque to 35 ft. lbs.

15 Wait 10 – 15 minutes then recheck final torque of 35 ft. lbs. on the head bolts using the same sequence.

#### PARTS LIST

<u>PART #</u>	<u>DESCRIPTION</u>	<u>QTY.</u>
3000-01	TWIN CAM CYLINDER STUD 3/8-16 X 6.325"	8
3000-02	HEAD BOLT (SHORT) 1.875"	4
3000-03	HEAD BOLT (LONG) 3.175"	4
3000-04	565 THREAD SEALANT .20 OZ.	1
3000-05	MOLY ASSEMBLY LUBRICANT .5 OZ.	1
3025-01	EVO CYLINDER STUD 3/8-16 X 6.675"	8

#### WARRANTY:

All parts are guaranteed to the original purchaser to be free of manufacturing defects in materials and workmanship for a period of twelve (12) months from the date of purchase. Merchandise that fails to conform to these conditions will be repaired or replaced at FOP's option if the parts are returned to FOP by the purchaser within the (12) month warranty period.

In the event warranty service is required, the original purchaser must notify FOP of the problem immediately. Some problems may be rectified by a telephone call and need no further action. A part that is suspect of being defective must not be replaced without prior authorization from FOP. If it is deemed necessary for FOP to make an evaluation to determine whether the part was defective, it must be packaged properly to avoid further damage, and be returned prepaid to FOP with a copy of the original invoice of purchase and a detailed letter outlining the nature of the problem, how the part was used and the circumstances at the time of failure. After an evaluation has been made by FOP and the part was found to be defective, repair, replacement or refund will be granted.

#### ADDITIONAL WARRANTY PROVISIONS:

FOP shall have no obligation in the event an FOP part is modified by any other person or organization, or if another manufacturer's part is substituted for one provided by FOP. FOP shall have no obligation if an FOP part becomes defective in whole or in part as a result of improper installation, improper break-in or maintenance, improper use, abnormal operation, or any other misuse or mistreatment.

FOP shall not be liable for any consequential or incidental damages resulting from the failure of an FOP part, the breach of any warranties, the failure to deliver, delay in delivery, delivery in non-conforming condition, or any other breach of contract or duty between FOP and the customer. The installation of parts may void or otherwise adversely affect your factory warranty. In addition, such installation and use may violate certain federal, state and local laws, rules and ordinances as well as other laws when used on motor vehicles operated on public highways, especially in states where pollution laws may apply. Always check with federal, state, and local laws before modifying your motorcycle. It is the sole and exclusive responsibility of the user to determine the suitability of the product for his/her use, and the user shall assume all legal, personal injury risk and liability and all other obligations, duties and risks associated therewith. Our high performance parts, engines and motorcycles are intended for experienced riders only. Feuling Oil Pump Corporation reserves the right to change prices and/or discounts without notice and to bill at the prevailing prices at the time of shipments.

The words Harley®, Harley-Davidson® and H-D® and all H-D® part numbers and model designations are used in reference only. Feuling Oil Pump Corporation is in no way associated with, or authorized by Harley-Davidson Motor Co®. to manufacture and sell any of the engine parts described in this instruction sheet.

17215 ROPER STREET, MOJAVE CA 93501 PH. 619-917-6222 FAX 760-487-1545  
WWW.FEULINGPARTS.COM